

CLAIMS

1. A method of forming a conductive pattern,
comprising the steps of:

(1a) applying a positive, energy-sensitive paste

5 composition containing a conductive powder to a substrate,
followed by drying, to form a positive, energy-sensitive
coating;

(2a) irradiating the coating with active energy rays or
heat rays directly or through a mask so as to obtain a
10 desired pattern; and

(3a) removing the irradiated part of the coating by
development to form a conductive pattern coating.

2. A method according to Claim 1, wherein the
positive, energy-sensitive paste composition is a positive,
15 visible light-sensitive paste composition.

3. A method according to Claim 1, wherein the
positive, energy-sensitive paste composition is a positive,
ultraviolet-sensitive paste composition.

4. A method according to Claim 1, wherein the
20 positive, energy-sensitive paste composition is a positive
thermosensitive paste composition.

5. A method according to Claim 1, wherein the
positive, energy-sensitive paste composition further
contains a heat-fusible inorganic powder and wherein
25 calcination is carried out after Step (3a).

20250725 09:58:50

~~7.~~ A method of forming a conductive pattern,
comprising the steps of:

(2b) superimposing the dry film onto a substrate in such a manner that the surface of the positive, energy-sensitive layer is in contact with the substrate, to form a positive, energy-sensitive coating, and then peeling off the release film;

(4b) removing the irradiated part of the coating by development to form a conductive pattern coating.

9. A method according to Claim 7, wherein the positive, energy-sensitive paste composition is a positive, ultraviolet-sensitive paste composition.

25 10. A method according to Claim 7, wherein the

11. A method according to Claim 7, wherein the positive, energy-sensitive paste composition further contains a heat-fusible inorganic powder and wherein calcination is carried out after Step (4b).

~~13.~~ A method of forming a conductive pattern,
10 comprising the steps of:

15 (2c) superimposing the dry film onto a substrate in such a manner that the surface of the positive, energy-sensitive layer is in contact with the substrate, to form a positive, energy-sensitive coating;

(4c) peeling off the release film, and removing the irradiated part of the coating by development to form a conductive pattern coating.

25 14. A method according to claim 13, wherein the

positive, energy-sensitive paste composition is a positive, visible light-sensitive paste composition.

15. A method according to claim 13, wherein the positive, energy-sensitive paste composition is a positive, ultraviolet-sensitive paste composition.

16. A method according to Claim 13, wherein the positive, energy-sensitive paste composition is a positive, thermosensitive paste composition.

17. A method according to Claim 13, wherein the positive, energy-sensitive paste composition further contains a heat-fusible inorganic powder and wherein calcination is carried out after Step (4c).

18. A method according to Claim 17, wherein the heat-fusible inorganic powder is a glass frit.

20220225 09:23:03